



P	LED	EM	ECA
PART L	SKA	L85	



Fillit (Surface + Suspended) [Profile Systems]

07/12/2021

The Fillit is a linear lighting solution, housed in an aluminium extrusion, it has no visible fixings for an attractive minimalist look. The Fillit is able to provide seamless continuous lengths of light. Available in two sizes and a range of lengths, the Fillit is suited to a wide range of applications. L85 @ 50,000 hours. SDCM>3. CRI>80 (CRI>90 available on request).

Standard products

product code	dimensions	lens	output	power	efficacy	weight	IP rating
FLS085-B-GC--	L:850 W:70 H: 70	Microprismatic	3299	28.8	114.55	2.1	IP 40

Variations

type	suffix	symbol
Mini [50x67mm] Version	M	
Standard [70x70mm] Version	T	
RAL9003 [Signal White] Paint Finish	N	
RAL9010 [Pure White] Paint Finish	C	
RAL9016 [Traffic White] Paint Finish	W	
RAL9006 [White Aluminium] Paint Finish	S	
RAL9005 [Jet Black] Paint Finish	B	
3000K Colour Temperature	3K	
4000K Colour Temperature	4K	
Tunable White Colour Temperature	TU	
Fixed Output	FO	
DALI	D3	
Casambi	CA	
No Emergency		
3 Hour Emergency Facility	E	
3 Hour Central Test Emergency Facility (DALI EM Pro)	D	
-		
2pt Suspension Kit	2SK	