



| | | | |
|-----------|-----|-----|-----|
| P | LED | EM | ECA |
| PART L | SKA | L85 | |



Fillit (Surface + Suspended) [Profile Systems]

07/12/2021

The Fillit is a linear lighting solution, housed in an aluminium extrusion, it has no visible fixings for an attractive minimalist look. The Fillit is able to provide seamless continuous lengths of light. Available in two sizes and a range of lengths, the Fillit is suited to a wide range of applications. L85 @ 50,000 hours. SDCM>3. CRI>80 (CRI>90 available on request).

Standard products

| product code | dimensions | lens | output | power | efficacy | weight | IP rating |
|---------------|-------------------|------|--------|-------|----------|--------|-----------|
| FLS197-E-UD-- | L:1970 W:70 H: 70 | Opal | 4393 | 38.1 | 115.30 | 5.0 | IP 40 |

Variations

| type | suffix | symbol |
|--|--------|--------|
| Mini [50x67mm] Version | M | |
| Standard [70x70mm] Version | T | |
| RAL9003 [Signal White] Paint Finish | N | |
| RAL9010 [Pure White] Paint Finish | C | |
| RAL9016 [Traffic White] Paint Finish | W | |
| RAL9006 [White Aluminium] Paint Finish | S | |
| RAL9005 [Jet Black] Paint Finish | B | |
| 3000K Colour Temperature | 3K | |
| 4000K Colour Temperature | 4K | |
| Tunable White Colour Temperature | TU | |
| Fixed Output | FO | |
| DALI | D3 | |
| Casambi | CA | |
| No Emergency | | |
| 3 Hour Emergency Facility | E | |
| 3 Hour Central Test Emergency Facility (DALI EM Pro) | D | |
| - | | |
| 2pt Suspension Kit | 2SK | |